

Item #	
Project	
Date	




Model # D35 Triple Bowl Premix Dispensers Features

- Famous two-piece, stainless steel, dripless pouring valves are sanitary and easy to use and maintain.
- Better design and more stainless steel allow easier cleaning and less maintenance.
- Superior engineering allows full beverage cooling right down to the last drink.
- Large, 5 gallon bowls, with easy to read measuring marks, are separate to allow bowl cleaning and flavor changes without "total system shut-down".
- Super-strong, virtually unbreakable polycarbonate bowls and covers give lasting durability.
- Unique evaporator and high efficiency pump cools faster and more efficiently for faster start-ups.
- Choice of Regular (-4) or optional Stainless Steel (-3) side panels and drain trays.
- Down-to-earth design engineering makes routine servicing easier and simpler.
- Second-to-none quality with "field condition" testing.
- Optional whipper for frothed drinks.
- Agitators are included with each unit for fresh juices, coffees or teas.
- World-wide sales and service assure customer satisfaction.





Crathco_® Model # D35 Triple Bowl **Premix Dispensers**



Specifications	D35 (115V/60Hz)	D355 (230V/50Hz)	D356 (230V/60Hz)
# Bowls	3	3	3
Bowl Capacity	5 gallons (18.9L)	5 gallons (18.9L)	5 gallons (18.9L)
Refrigeration	1/3 hp	1/3 hp	1/3 hp
Volts / Hz / Amps	115V / 60Hz / 8.5Amp	230V / 50Hz / 4.3Amp / 989 Watts	230V / 60Hz / 4.3Amp / 989 Watts
Dimensions	27 1/4" x 25 5/8" x 15 7/8"	27 1/4" x 25 5/8" x 15 7/8"	27 1/4" x 25 5/8" x 15 7/8"
(H x W x D)	(69 cm x 65 cm x 40 cm)	(69 cm x 65 cm x 40 cm)	(69 cm x 65 cm x 40 cm)
Ship Weight (2 boxes)	95 lbs (base: 71, bowls: 24)	95 lbs (base: 71, bowls: 24)	95 lbs (base: 71, bowls: 24)
	43 kg (base: 32.2, bowls: 10.8)	43 kg (base: 32.2, bowls: 10.8)	43 kg (base: 32.2, bowls: 10.8)
Cup Height	8-1/4" (21 cm)	8-1/4" (21 cm)	8-1/4" (21 cm)
Listings	UL, NSF, CUL	NSF, CE	NSF, CE

Specifications are subject to improvement or change without notice.

Standard Op	tions*								
Side panels & drip	,	-3 Stainless steel material (additional charge), -4 off-white high impact plastic (standard - no additional charge)							
Valve cap (part# 2	039)	Improves sealing of valve when using pulpy products							
Valve locking box (part# 2502) (use w/ standard handle) Secures		cures the valve from dispensing during off-hours - not to be used with non-contact handle							
Liquid Auto Fill (pa	art# 90295)	Ensures proper product and mixing consistency, maintains optimum product level in bowls, eliminates need for frequent manual m					frequent manual mixing		
Shipboard kit (part# 5925) Makes u			es unit safer for installation aboard marine vessel; only available for use with agitator						
Milk Fat Impellers Use with			with milk-based products, and/or products with heavy pulp						
Condensation Cor	ensation Control Direct and conceal condensation in high humidity or outdoor locations								
Custom Optio	ons * (available	with m	ninimum purchase quar	ntity)					
Frosted Bowls 5 ga	al. (18.9L)	Frosted	surface simulates condens	sation while helping hide p	product residue and offeri	ng added UV protection.			
Frosted Lid Lid with		id with frosted surface for use with 5 gallon (18.9L) frosted bowls							
Whippers (must be ordered when ordering machine) Great (see models in spec chart below) Great		Great f	Great for iced cappuccinos and iced coffee. Whips beverage upon dispensing to create a frothy top on drink.						
	1WD35 (115V/6 (3 bowls - 1 whip		2WD35 (115V/60Hz) (3 bowls - 2 whippers)	3WD35 (115V/60Hz) (3 bowls - 3 whippers)	1WD355 (230V/50Hz) (3 bowls - 1 whipper)	2WD355 (230V/50Hz) (3 bowls - 2 whippers)	3WD355 (230V/50Hz) (3 bowls - 3 whippers)		
Bowl Capacity	5 gallons (18.9L)		5 gallons (18.9L)	5 gallons (18.9L)	5 gallons (18.9L)	5 gallons (18.9L)	5 gallons (18.9L)		
Refrigeration	1/3 hp		1/3 hp	1/3 hp	1/3 hp	1/3 hp	1/3 hp		
Volts / Hz / Amps	115V / 60Hz / 9.1	IAmp	115V / 60Hz / 9.7Amp	115V / 60Hz / 10.3Amp	230V / 50Hz / 4.6Amp	230V / 50Hz / 4.9Amp	230V / 50Hz / 5.2Amp		
Dimensions (H x W x D)	29 3/4" x 25 5/8" x (76cm x 65cm x 4		29 3/4" x 25 5/8" x 15 7/8" (76cm x 65cm x 40cm)	29 3/4" x 25 5/8" x 15 7/8" (76cm x 65cm x 40cm)	29 3/4" x 25 5/8" x 15 7/8" (76cm x 65cm x 40cm)		29 3/4" x 25 5/8" x 15 7/8" (76cm x 65cm x 40cm)		
Ship Weight (2 boxes)	97 lbs (74 lbs, 23 44 kg (33.5 kg, 1	,	98 lbs (76 lbs, 22 lbs) 44.5 kg (34.5 kg, 10 kg)		97 lbs (74 lbs, 23 lbs) 44 kg (33.5 kg, 10.5 kg)	98 lbs (76 lbs, 22 lbs) 44.5 kg (34.5 kg, 10 kg)	100 lbs (78 lbs, 22 lbs) 45.4 kg (35.4 kg, 10 kg)		
Cup Height	5-1/2" (14 cm)		5-1/2" (14 cm)	5-1/2" (14 cm)	5-1/2" (14 cm)	5-1/2" (14 cm)	5-1/2" (14 cm)		
Listings	UL, NSF, CUL		UL, NSF, CUL	NSF, UL, CUL	NSF, CE	NSF, CE	NSF, CE		

* Additional cost applies





Specifications are subject to improvement or change without notice.

Tel (502) 425-4776 • Fax (502) 425-4664 • 1-800-695-4500 (USA & Canada only) P.O. Box 35020 • Louisville, KY 40232 • USA www.grindmaster.com • email: info@grindmaster.com

CE