WELLS LAMONT

Industrial

PRODUCT SPECIFICATION SHEET

PRODUCT INFORMATION

Style: Kevlar Standard Sleeve

Size Part #
Sizing:

Standard Thumb Hole SK-10 SK-10H 10" 14" SK-14 SK-14H 16" SK-16 SK-16H 18" SK-18 SK-18H 22" SK-22 SK-22H 24" SK-24 SK-24H

Classification: Cut Resistant



PRODUCT DESCRIPTION

Description: Kevlar® Standard Sleeve

Color: Yellow

Material: 100% Kevlar (2-ply knit)
Wrist: With or Without a Thumb Hole

Sold by: Dozen Pieces
Packaging (Inner Pack): 12 Pieces
Packaging (Case Pack): 288 Pieces

CUT PROTECTION PERFORMANCE INFORMATION

Test Method: ASTM F1790-97
Test Results: 1207 grams / 2.66lbs.

ANSI Level 3

ABRASION PROTECTION PERFORMANCE INFORMATION

Test Method: ASTM D3884-05
Test Results: 388 revs (cycles)

WASHING INSTRUCTIONS

Always wash similar products of the same materials together. This will eliminate different material types from being effected by non-recommended chemicals. Rinse all gloves thoroughly in cold water to ensure the release of particles in the products. If pre-soaking use luke warm water to ensure good particle softening. Mild detergents or chemicals should be used to enhance the laundering process. All products should be laundered using a mild soap and detergent. Use a warm water wash with a temperature not to exceed 160°F (71°C). Wash time should not be longer than 15 to 20 minutes. Use a rinse cycle for the product in cold water. Repeat above as often as needed to ensure a thoroughly clean product. It is important to use a high extraction speed to thoroughly remove all excess moisture. Tumble dry glove in a temperature not higher than 150°F (67°C) for a time of 15 to 20 minutes; adjustments in dry time may increase depending on quantity and weight of the products. Temperatures should not exceed 150°F (67°C).

CAUTION

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.

Wells Lamont Industrial 6640 W Touhy Ave Niles IL 60714
Toll-Free 1.800.247.3295 Fax 1.847.470.1026 www.wellslamontindustrial.com

JC 7/12