

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

Model : TOS-50PN-W(B)

Sandwich & Cheese Display Cases

Open Display Merchandisers

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess



TOS-50PN-W

___ FEATURES & BENEFITS =__

■ Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

■ High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

- Exterior and bottom glass shelf is white (black) with a mirror finish.
- Digital temperature controller
- Single pane glass is tempered for safety
- Stainless steel airflow grille
- Self-contained system, no plumbing required











Model	CU./FT.	НР	AMPS	Crated Weight (lbs.)	L x D x H* (inches)
TOS-50PN-W(B)	8.1	1/3	8	625	50 x 353/8 x 34

(unit: inch)

Sandwich & Cheese Display Cases

Model: TOS-50PN-W(B)

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type				
Full Load Amperes	8			
Compressor HP	1/3			
Cord Length (ft.)	81/4			
Refrigerant	R-290			
DIMENSIONAL DATA				
Net Capacity (cu. ft.)	8.1			
Ext. Length Overall (in.)	50 (1270mm)			
Ext. Depth Overall (in.)	35 _{3/8} (900mm)			
Ext. Height Overall (in.)*	34 (863mm)			
Int. Length Overall (in.)	45 _{1/2} (1155mm)			
Int. Depth Overall (in.)	28 _{1/8} (715mm)			
Int. Height Overall (in.)	63/4 (172mm)			
Int. Height Load limit (in.)	31/2 (90mm)			
Net Weight (lbs.)	425			
Gross Weight (lbs.)	625			

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

2 Year Parts and Labor Warranty **WARRANTY: Additional 3 Year Warranty on Compressor**


STANDARD FEATURES

- · White and black color come standard
- 3" dia. swivel casters with locks on the rear set
- ** Lead time applies. Please contact your sales representative for more details to order.


■ Recommended operating conditions

TOS models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively. Keep the cycle air duct area clear of objects for optimal cooling.


PLAN VIEW



TOP VIEW



FRONT VIEW



Ver.20200721













■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519

■ Warranty: 800-381-7770 ■ AC: 888-900-1002











^{*} Height does not include 2-1/4" for caster height.