## WELLS LAMONT

Industrial

### PRODUCT SPECIFICATION SHEET



## PRODUCT INFORMATION

**VS 13** Style:

Part # **Overedge** <u>Size</u> Sizing: White Gray **XSmall** 135027 135042 Green Small 135028 135037 Yellow Medium 135029 135038 Blue 135030 135039 White Large 135031 135040 Orange XLarge

**Registered Brand Name:** Whizard® Cut Resistant Classification:



## PRODUCT DESCRIPTION

**Description:** Wireless Cut Resistant Glove Color: Available in White or Gray

Material: High Performance Fibers; Wireless

CFR 21 - Approved for Food Contact

Sold by: Piece Packaging (Inner Pack): 6 Pieces Packaging (Case Pack): 120 Pieces

# **CUT PROTECTION PERFORMANCE INFORMATION**

Test Method: ASTM F1790-97 Test Results: 1541 grams / 3.40lbs.

ANSI Level 4

## ABRASION PROTECTION PERFORMANCE INFORMATION

Test Method: ASTM D3884-05 Test Results: 710 revs (cycles)

#### WASHING INSTRUCTIONS

Always wash similar products of the same materials together. This will eliminate different material types from being effected by non-recommended chemicals. Rinse all gloves thoroughly in cold water to ensure the release of particles in the products. If presoaking use luke warm water to ensure good particle softening. Mild detergents or chemicals should be used to enhance the laundering process. All products should be laundered using a mild soap and detergent. Use a warm water wash with a temperature not to exceed 160°F (71°C). Wash time should not be longer than 15 to 20 minutes. Use a rinse cycle for the product in cold water. Repeat above as often as needed to ensure a thoroughly clean product. It is important to use a high extraction speed to thoroughly remove all excess moisture. Tumble dry glove in a temperature not higher than 150°F (67°C) for a time of 15 to 20 minutes; adjustments in dry time may increase depending on quantity and weight of the products. Temperatures should not exceed 150°F (67°C).

### **CAUTION**

Gloves are cut resistant but are not cut or puncture-proof. Do not subject to high-speed, serrated blades or intentional slashings.

Wells Lamont Industrial 6640 W Touhy Ave Niles IL 60714 Toll-Free 1.800.247.3295 Fax 1.847.470.1026 www.wellslamontindustrial.com

JC 7/12