

PPC-200W-II Series

Washdown Portion Control Scales

- IP65 washdown in battery mode
- Checkweighing, basic weighing, and tare functions
- Programmable auto-off
- Pound, pound-ounce, ounce, kilogram



Heavy-duty ABS
construction



9.1in x 9.1in
stainless-steel
platform

Easy-to-read
LCD display

MODEL	PPC-200W-II-4	PPC-200W-II-10	PPC-200W-II-20	PPC-200W-II-40
Capacity	4lb x 0.002lb 2kg x 0.001kg 80oz x 0.05oz 5lb x 0.05oz*	10lb x 0.005lb 4kg x 0.002kg 160oz x 0.1oz 10lb x 0.1oz*	20lb x 0.01lb 10kg x 0.005kg 320oz x 0.2oz 20lb x 0.2oz*	40lb x 0.02lb 20kg x 0.01kg 800oz x 0.5oz 50lb x 0.5oz*
Weighing System	Strain gauge load cell			
Certificate of Conformance	22-004 (US) AM-6199 (Canada)			
Platform	9.1in x 9.1in (230mm x 230mm), stainless steel, removable			
Display	5-digit, 7-segment LCD plus annunciators			
Character Size	0.9in x 0.5in (23mm x 12mm)			
Power	"D" size batteries (qty. 6) or AC adapter (included)			
Battery Life	3000 hours of continuous use			
Housing Material	ABS with stainless-steel platform			
Operating Temperatures	14°F ~ 104°F (-10°C ~ 40°C)			
Functions	Basic weighing, gross/net weighing, tare, checkweighing, batching			
Options	RS-232 serial communication			

*Combined units, such as pound-ounce, are not legal for trade.

Dimensions

